



**SPORTS LINE
MARKING SPECIALISTS**

www.fleetaustralasia.co.nz

PRODUCT INFORMATION

Safety Data Sheet

1. COMPANY PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:

FLEET COLOUR XS

PRODUCT PURPOSE:

ALL COLOURS

COMPANY IDENTIFICATION:

LINE MARKING (OUTDOOR)
FLEET AUSTRALASIA LIMITED
20 Hinau Street
Wanganui 4501
New Zealand
+64 6 349 0100
+64 6 349 2770
+64 0508 4 35338

TEL:

FAX:

EMERGENCY TELEPHONE

2. COMPOSITION

Vinyl Acrylic water-based line marking paint.

3. HAZARD IDENTIFICATION

PRIMARY ROUTES OF EXPOSURE:

Eye Contact

Skin Contact

EYE CONTACT:

Direct contact with this material may cause irritation.

SKIN CONTACT:

Prolonged or repeated contact may cause irritation of the skin.

4. FIRST AID MEASURES

EYE CONTACT:

Flush eyes with large amounts of water, before marking fluid dries, for at least 10 minutes.

SKIN CONTACT:

Seek medical advice if irritation persists.

Remove contaminated clothing. Wash with soap and water before fluid dries.

INGESTION:

Drink plenty of water. Do not induce vomiting. Seek medical advice.

5. FIRE FIGHTING MEASURES

Aqueous dispersions will not burn. Dried films are combustible. Material will spatter above 100°C.

FLASH POINT:

Non-combustible

AUTO-IGNITION TEMPERATURE:

Not Applicable

EXTINGUISHING AGENTS:

Water, foam, carbon dioxide or dry powder extinguishers are all suitable.

6. ACCIDENTAL RELEASE MEASURES

Spillage should not be washed into any drain unless it leads to a suitable effluent treatment process. Residues and spillage should be soaked up with an inert absorbent (e.g. sand, earth) for disposal.

7. HANDLING AND STORAGE

HANDLING:

Handle in accordance with good industrial safety and hygiene practices.

STORAGE:

Keep from freezing; product may coagulate.

Store in sealed containers between 5°C and 30°C.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

EXPOSURE CONTROLS:

Local exhaust ventilation may be required in circumstances where the product is sprayed, heated or dried in confined spaces.

PERSONAL PROTECTION:

Respiratory:

If sprayed in confined spaces e.g. indoors, masks may be required.

Hand:

Gloves, if risk of skin contact.

Eye:

Goggles, if risk of splashing.

Skin:

Standard industrial overalls if risk of splashing.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Flowable Liquid
Odour:	Slight
pH:	7.5 to 8.5
Boiling point:	Approx. 100°C
Specific Gravity:	1.0 to 1.2 g/cm ³
Water solubility:	Fully miscible

10. STABILITY AND REACTIVITY

Fleet Colour XS is stable under normal conditions of use - also see Handling and Storage.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity:	LD ₅₀ (RAT) > 2000 mg/kg Method : EEC 84/449, B.1
Irritant effect on skin:	Slight (Rabbit) Method : EEC 84/449, B4
Irritant effect on skin :	Slight (Rabbit) Method : EEC 84/449, B5

The product is therefore considered to be of low acute oral toxicity to mammals.
Frequent contact may lead to skin and eye irritation, especially if the product is allowed to dry out.

Long term experience of handling of this product under Industrial conditions indicates the absence of any chronic or acute effects. This product is considered to be harmless to health if used in the correct manner.
The toxicological data given are determined by analogy.

12. ECOLOGICAL INFORMATION

Chemical Oxygen Demand (C.O.D):	800 mg/l
(washdown, i.e., low concentration @ <500mg/l).	

Severn Trent Water Authority determined the ecological data given.
Fleet Colour XS paint is totally miscible with water and at low concentrations, exhibits low toxicity to fish. According to experience, this product has no harmful effect to the environment if used in the correct manner.

13. DISPOSAL INFORMATION

Fleet Colour XS is not classified as hazardous waste. This products can be coagulated and separated from the aqueous phase for landfill or incineration. The residual liquid should not be discharged without prior consent. Existing EEC, National and Local Regulations must always be complied with.

14. TRANSPORT INFORMATION

Fleet Colour XS is not classified as hazardous for transportation.

15. REGULATORY INFORMATION

EEC Hazard Classification:	None
----------------------------	------

16. OTHER INFORMATION

Fleet Australasia Ltd, classify this products as non-hazardous or toxic under normal conditions of use.
The information provided in this Safety data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be carried out and should not be construed as a guarantee of specific properties.

Date of issue:	March 27 2013	Revision Reference:	002
----------------	---------------	---------------------	-----